

Foreground Music Speaker

FS415 : 4" 10W 100V Line
FS630 : 6" 30W 100V Line



White and black colour available

Available in 4" and 6" of driver size complete with matching transformer and mounting bracket. They are suitable for foreground soft music such as restaurants, shops and general sound reinforcement in meeting room, corridors, etc.

Foreground Music Speaker

FS520 : 5" 15W 100V Line
FS625 : 6" 25W 100V Line



Only black colour available

These models deliver wider frequency range from bass to treble for satisfying a more demanding audience. Among applications includes bars, restaurants, function halls and could easily complement any sound reinforcement systems.

Cabinet Array Speaker

LA4100 : 4" 120W 100V Line



Only black colour available

LA4100 is array speaker built with 4" driver delivering a punch of 120W of output with dispersion angle of H120 x V60 degree and high SPL. Most suitable for application like mosques, halls, public areas such as bus stations, airports, etc where speech clarity is utmost important.

TECHNICAL SPECIFICATIONS

	FS415	FS630	LA4100	FS520	FS625
SPEAKER					
Power rating	10 W	30 W	120 W 100V	15 W	25 W
Diameter	4" (100mm)	6" (150mm)	4"	5" (125mm)	6" (150mm)
Speaker type	2 way speaker		Single cone	2 way speaker	
Impedance	8 Ohm		8 Ohm	8 Ohm	
Freq response (+/- 5dB)	95 ~ 16 KHz	85 ~ 19 KHz	130 ~ 18 KHz	85 ~ 16 KHz	80 ~ 15 KHz
SPL @ 1W / m (+/- 3dB)1KHz	85 dB	88 dB	96 dB	87 dB	89 dB
TRANSFORMER					
Tapping (100V line)	10 W	30 W	60 / 120 W	15 W	25 W
Primary impedance	1 K Ohm	330 Ohm	167 / 83 Ohm	667 Ohm	400 Ohm
Secondary impedance	8 Ohm		8 Ohm	8 Ohm	
MECHANICAL					
Grille / enclosure	ABS enclosure		Polypropelyne (PP)	ABS enclosure	
Overall size (WxHxD) mm	160 x 220 x 140	215 x 295 x 190	205 x 585 x 195	169 x 266 x 160	212 x 328 x 190
Weight	1.1 kg	2.8 kg	21 kg	2.1 kg	3.0 kg
Colour	White and Black available		Black	White and Black available	

packing information

FS415 : 415 (W) x 380 (H) x 540 (D) mm
 9.8 kg 8 uts per carton
 FS630 : 640 (W) x 415 (H) x 495 (D) mm
 25.5 kg 8 uts per carton

LA4100 : 485 (W) x 665 (H) x 275 (D) mm
 21 kg 2 uts per carton

FS520 : 415 (W) x 380 (H) x 540 (D) mm
 18.7 kg 8 ut per carton
 FS625 : 640 (W) x 415 (H) x 495 (D) mm
 26 kg 8 ut per carton